

VariKIOSK 217

17.3" Desktop Self-Service Kiosk



Features

- / Fully integrated AIO desktop self-service kiosk.
- / Support Intel® 12th Generation Core i3 CPU.
- / Intel® TPM protect system & data with software-based security hardening.
- / True flat 17.3" 9:16 LCD, 300 nits brightness with front bezel IP54 dust & spill water resistant.
- / RAID 0/1 function with dual SSD/HDD support (Option).
- / Durable die-cast aluminum chassis; built to last.
- / Redefines serviceability from design with easy access & quick swap modular design for SSD/HDD & MB box.
- / Integrated mPOS/scanner holder for easy use and counter space saving.



Specification

Model Name		VariKIOSK 217
Motherboard code		PE26
Main Board	Processor	Intel® Core™ i3-1215U Processor 10M Cache, up to 4.40 GHz
	Chipset	CPU Integrated
	System Memory	1 x SO-DIMM DDR5 slot, 8GB RAM as standard. Max. memory support up to 32GB
	TPM	Intel® TPM 2.0
Display & Touch	LCD Size	17.3" 16:9 TFT LCD(LED backlight)
	Brightness	300nits
	Resolution	1920 x 1080
	Touch Technology	True Flat Projected Capacitive Technology
Storage	SSD	256G
	RAID Function	TBD
Motherboard I/O & Expansion	DC Input	1 x Mini Din 4P (DC 19V only)
	Cash Drawer	1 x RJ-11 (Support DC +12V or +24V (default)) port supports 2 cash drawers
	LAN port	1 x Gigabit Ethernet by RJ-45
	USB port	3 x USB 2.0, 3 x USB 3.1
	COM port	3x COM (COM1/2: RJ48 support DC+0/5/12v by BIOS setting, default setting is 0v. COM3: DB-9)
	VGA port	1 x DB-15 VGA port Power enable by BIOS setting (default disable)
	Bus Expansion	1 x M.2 M Key for SSD 1 x M.2 E Key for WiFi
	Power Switch	1 x power on / off switch button
	Speaker	HD Audio, 2W Speaker x 2
	Type-C	1 x Type C (PD + DP)
OS Support	Win 11 IoT GAC	
Power Adapter	DC+19V, 180watt (Power USB)	
Compliance	Certifications	CE, FCC, LVD, RoHS
	Protection	IP54 on front panel
Material	Main Unit: Die-Cast Aluminum ; I/O Cover:Plastic	
Color	White	
Dimension(W x H x D)	Main Unit: 270 x 608.7 x 234.6	
	Main Unit + Peripherals: 377.6 x 608.7 x 234.6	
Weight	12Kg	
Environmental	Operating Condition	0°C ~ 40°C, 10% ~ 90% RH, non-condensing
	Storage Condition	-20°C ~ 60°C, 10% ~ 90% RH, non-condensing

Poindus Systems Corp.

Taiwan (HQ) | Germany | UK | Iberica

5F., No. 59, Ln. 77, Xing-Ai Rd., Neihu Dist., Taipei City 114, Taiwan. R.O.C.

☎ +886 2 7721 4688 📠 +886 2 7721 2289 ✉ sales@poindus.com

Poindus
COMPAL GROUP